

Material Safety Data Sheet.
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)
BERG COLOR TONING SYSTEM

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

| | |
|---|---|
| Manufacturer's Name Berg Color-Tone, A Div. of Omega | Emergency Telephone Number 800-777-6634 |
| Address (Number, Street, City, State, and ZIP Code) 1041 S. Carroll St. | Telephone Number for Information 410-374-3250 |
| Hampstead, MD 21074 | Date Prepared February 23, 2009 |
| | Signature of Preparer (optional) |

Section II — Hazardous Ingredients/Identity Information

| Hazardous Components (Specific Chemical Identity; Common Name(s)) | OSHA PEL | ACGIH TLV | Other Limits Recommended | % (optional) |
|---|----------|----------------------|--------------------------|--------------|
| Acetic acid | | 10 ppm (TWA) | | |
| Isopropyl alcohol | | 400 ppm (TWA) | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

Section III — Physical/Chemical Characteristics

| | |
|--|--|
| Boiling Point About 212°F | Specific Gravity (H ₂ O = 1) Like water |
| Vapor Pressure (mm. Hg.) n/a | Melting Point Like water |
| Vapor Density (AIR = 1) n/a | Evaporation Rate (Butyl Acetate = 1) Like water |
| Solubility in Water Totally miscible | |
| Appearance and Odor No odor. Various colors. | |

Section IV — Fire and Explosion Hazard Data

| | | | |
|---|------------------|-----|-----|
| Flash Point (Method Used) Not flammable | Flammable Limits | LEL | UEL |
| Extinguishing Media n/a | | | |
| Special Fire Fighting Procedures n/a | | | |
| Unusual Fire and Explosion Hazards n/a | | | |

