Material Safety Data Sheet	MT2 CARBON TONER	1/5
According to 91/155 EC		

## 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Chemical name/ Trade name: MT2 CARBON

Application/use: Photographic toner

Company name: Moersch Photochemie, Am Heideberg 48

D 50354 Hürth, Germany

**Telephone:** ++49 22 33 943137 **Helth Emergency Phone:** ++49 22 33 943137

#### 2 HAZARDS IDENTIFICATION

**CONTAINS: Sodium Sulfide** 

DANGER!

CONTACT WITH ACID LIBERATES FLAMMABLE AND POISONOUS GAS

**CAUSES SKIN AND EYE BURNS** 

DUST, MIST OR VAPOUR IRRITATING TO THE EYES AND RESPIRATORY TRACT

HARMFUL IF INHALED, ABSORBED THROUGH SKIN, OR SWALLOWED

NFPA Hazard Ratings: Health - 3, Flammability - 1, Instability - 0

NOTE: NFPA 704 (2001) hazard indexes involves data review and interpretation that may vary among companies. It is intended only for rapid, general identification of the magnitude of the potential hazards.

To adequately address safe handling, ALL information in this MSDS must be considered.

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

This product is a preparation according to the law for chemicals.

Description: Aqueous solution containing inorganic and organic substances

Name	Content	CAS	EINECS	CLASSIFICATION
SODIUM SULFIDE	10-15	27610-45-3	215-211-5	T, N;R-23/25-33-50/53
SODIUM SULFITE	10-15	7757-83-7	231-821-4	not classified
SODIUM SELENITE	>0,5%	10102-18-8	233-267-9	T, N;R-23/25-33-50/53

**Other information:** further principal ingredient: Water

## **4 FIRST-AID MEASURES**

**Inhalation:** If inhaled, move to fresh air. Get medical attention.

**Eyes:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention.

**Skin:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if symptoms occur. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes.

**Ingestion:** If swallowed, DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Material Safety Data Sheet	MT2 CARBON TONER	2/5
According to 91/155 EC		

## Notes to physician:

**Treatment:** Strong alkalis bind tissue protein. Following initial flushing of the eye with water, continued irrigation of the eye with saline is recommended. Treatment should be continued until pH of tears reaches neutral

### **5 FIRE-FIGHTING MEASURES**

**Extinguishing Media:** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. **Special Fire-Fighting Procedures:** Wear self-contained breathing apparatus and protective suit. Fire or excessive heat may produce hazardous decomposition products.

**Hazardous Combustion Products:** Carbon oxides, sulphur oxides, (see also Hazardous Decomposition Products section).

Unusual Fire and Explosion Hazards: None.

### **6 ACCIDENTAL RELEASE MEASURES**

**Methods for cleaning up:** Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination.

## **7 HANDLING AND STORAGE**

**Personal precautions:** Do not breathe vapours or spray mist. Keep container tightly closed. Do not get in eyes and avoid contact with skin and clothing. Use only with adequate ventilation. Wash thoroughly after handling.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials.

**Storage:** Keep container tightly closed. Keep away from incompatible substances (see Incompatibility section.)

## **8 OUTLINE DEMARCATION AND PERSONAL PROTECTION EQUIPMENT**

## Occupational exposure controls: Not established

**Ventilation:** Use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels to an acceptable level.

**Respiratory protection:** If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be worn. Respirator type: N95 Particulate Filter. A full-face positive-pressure air-supplied respirator must be worn if hazardous decomposition products are likely to be released or have been released. See Stability and Reactivity Section. If respirators are used, a program should be instituted to assure compliance with applicable federal, state, commonwealth, provincial, or local laws and regulations.

Eye protection: Wear safety glasses with side shields (or goggles) and a face shield.

**Skin and body protection:** Wear impervious gloves and protective clothing appropriate for the risk of exposure.

**Recommended Decontamination Facilities:** Safety shower, eye wash, washing facilities as appropriate to condition of use.

Material Safety Data Sheet	MT2 CARBON TONER	3/5
According to 91/155 EC		

### 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE liquid
COLOR dark red
ODOR sulphurous

**SOLUBILITY** 100% soluble in water

BOILING POINT (°C)

Melting Point

FLAMING POINT

Implementatory/

100°C - 212°F

less than 0°C - 32°F

Not applicable.

Not inflammable.

**Catching light temperature:** 

SELF FLAMMABILITY
FIRE PROMOTING QUALITIES
DANGER OF EXPLOSION

Not self-flammable
Not combustible.
No danger of explosion.

RELATIVE DENSITY 1.29 pH-VALUE, CONC. SOLUTION 12.4

### **10 STABILITY AND REACTIVITY**

**STABILITY:** Stable under normal conditions

**CONDITIONS TO AVOID:** Avoid contact with acids

Generates toxic gas in contact with acid.

**HAZARDOUS POLYMERISATION** Will not polymerize.

MATERIALS TO AVOID St

Strong acids. Strong alkalies. Avoid contact with other photographic

solutions and cleaning compounds.

# **HAZARDOUS DECOMPOSITION PRODUCTS**

sulphur oxides, hydrogen sulphide.

# 11 TOXICOLOGICAL INFORMATION

### **Effects of Exposure**

**Inhalation:** Harmful if inhaled. If hydrogen sulphide gas is liberated due to contact with acid, it may cause headache, nausea, dizziness, confusion, weakness, unconsciousness, convulsions, and death.

Eyes: Causes eye burns.

**Skin:** Harmful if absorbed through skin. Causes skin irritation.

**Ingestion:** Harmful if swallowed. If free gastric acidity is high, hydrogen sulfide is liberated in the stomach and may cause systemic toxic effects such as vomiting, respiratory depression, tremors, convulsions and death.

# **Acute Toxicity Data:**

Oral LD50 (rat): 1,600 mg/kg

Skin irritation: severe (The product may be absorbed through the skin.)

Skin irritation: Corrosive (4-hour DOT Skin Corrosivity Test, Destruction of skin tissue as a

result of more than 3 minutes exposure.)

Eye irritation: severe

### 12 ECOLOGICAL INFORMATION

Environmental data is not available.

## 13 INDICATIONS FOR WASTE MANEGEMENT

The corresponding local water-and waste regulations must be observed. Do not dispose with domestic garbage. Do not let it get into the sewage system.

Material Safety Data Sheet	MT2 CARBON TONER	4/5
According to 91/155 EC		

#### 14 TRANSPORT INFORMATION

IATA: UN Number: 3267

Proper shipping name: Corrosive liquid, basic, organic (Sodium sulfide)

Class: 8

Packaging group: II IMDG: UN Number: 3267

Proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC

(Sodium sulfide)

Class: 8

Packaging group: II

US DOT: UN Number: 3267

Proper shipping name: Corrosive liquid, basic, organic (Sodium sulfide)

Class: 8

Packaging group: II

### 15 REGULATIONS

#### Identification

The product is classified and labelled according to EC guidelines



## U.S. California Prop. 65: none

Carcinogenicity Classification (components present at 0.1% or more):

International Agency for Research on Cancer (IARC): none

American Conference of Governmental Industrial Hygienists (ACGIH): none

U.S. National Toxicology Program (NTP): none

U.S. Occupational Safety and Health Administration (OSHA): none

Chemical(s) subject to the reporting requirements of U.S. Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372: none

**Relevant R-phrases** 20/22 harmful by inhalation and if swallowed.

31 Contact with acids liberates toxic gas.

33 Danger of cumulative effects. 36/38 Irritating to eyes and skin.

S sentences: S-2 Keep out of reach of children.

S-26 In case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

S-36/37 Wear suitable protective clothing and gloves. S-46 If swallowed seek medical advice immediately and show this

container label.

61 Avoid release to the environment. Refer to special

instructions/safety data sheets.

Material Safety Data Sheet MT2 CARBON TONER 5/5
According to 91/155 EC

Remarks: This classification was carried out according to the calculation method

for preparations guideline (88/379/EEC).

Water endangering class 2 (water endangering) hazardous for water

### **16 OTHER INFORMATION**

Use: Photographic toner

## **Further information:**

These details refer merely on this above product and not needs to be valid, if this is occurred with another product or in an arbitrary process.

The information corresponds to our today's knowledge, it is correct and complete and with best conscience, given without a guarantee, though. It shall describe our product with a view to safety requirements and has therefore not the meaning to assure of certain qualities. The responsibility of the use of this product remains on the user whether the information is complete and suitable for his special use.

### **US/Canadian Label Statements:**

**CONTAINS: Sodium Sulfide** 

DANGER!

CONTACT WITH ACID LIBERATES FLAMMABLE AND POISONOUS GAS CAUSES SKIN AND EYE BURNS

DUST, MIST OR VAPOUR IRRITATING TO THE EYES AND RESPIRATORY TRACT HARMFUL IF INHALED, ABSORBED THROUGH SKIN, OR SWALLOWED

Do not breathe vapours or spray mist.

Do not get in eyes and avoid contact with skin and clothing.

Keep container tightly closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

**FIRST AID:** If inhaled, move to fresh air. Get medical attention. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes. If swallowed, DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. **Notes to physician:** Strong alkalis bind tissue protein. Following initial flushing of the eye with water, continued irrigation of the eye with saline is recommended. Treatment should be continued until pH of tears reaches neutral.

ISSUED BY: Wolfgang Moersch – Moersch-Photochemie

++49 2233 943137 info@moersch-photochemie.com

REVISION DATE: 11-06-2013 PRINTING DATE 11-06-2013